Teckentrup
Doors · Frames

Fire-resistant glass door
T30-FSA “Teckentrup GL”

NEW

Effective fire protection and aesthetic design.

The new fire protection door T30-FSA “Teckentrup GL” has been tested to conform with EN 1634-1 (DIN 4102) and therefore offers tried and tested fire protection. The frameless construction enables a maximum level of transparency that meets the current requirements for modern and aesthetically pleasing fire protection. Design-oriented fittings round off the high-quality look. The door is available in 1- and 2-leaf designs.

- Frameless fire protection door
- Maximum transparency
- High-quality elegance
- Fire-resistant
- Smoke-proof

Glass fire door in 1-leaf design: T30-1-FSA "Teckentrup GL"

Glass fire door in 2-leaf design: T30-2-FSA "Teckentrup GL"

TECHNICAL DATA

APPROVAL BY BUILDING AUTHORITIES:	Z-6.20-2184 tested in accordance with EN 1634-1 (DIN 4102)
INSTALLATION IN:	• masonry (at least 115 mm) • concrete (at least 100 mm) • Lightweight partition (at least 100 mm) • autoclaved aerated concrete (at least 115 mm)
APPROVED SIZES:	• 1-leaf: width: 600 - 1250 mm height: 800 - 2500 mm • 2-leaf: width: 1375 - 2500 mm height: 1750 - 2500 mm
FRAME:	Corner frame 1.5 mm thick with a 3-sided seal and floor bracket, Frame fixed with screws. Optional: frames can be supplied in the RAL of the customer's choice and in stainless steel.
SURFACE:	Stainless steel fitting cover 1.4301, polished 240-series grain stainless steel. Frame galvanised and primed, traffic white, (similar to RAL 9016)
QUALIFICATIONS:	• 1-/2-leaf design: smoke-proof in accordance with EN 1634-3/DIN 18095 with OTS • 1-leaf design: sound-insulated in accordance with DIN EN 20140/717-1 up to Rw 34 dB with retractable bottom seal
OPTIONAL EQUIPMENT: (FOR WHICH AN EXTRA CHARGE IS LEVIED)	• counter frame • closed frame and block frame • decals on the glass • screen printing in the interior of the pane • door drive



Glass door lock with switchover and elegant stainless steel round handle Latch set.

Elegant 3D special hinges with stainless steel cover individually adjustable.

A retractable bottom seal that is integrated into the glass construction.

Slide rail door closer compliant with DIN EN 1154 in stainless steel finish.

00/07/14 (GB) 129.573
We reserve the right to make technical changes. Product images are to be seen as examples.